

EA900Pro

1KVA ~ 3KVA
PF 0.9



Features


- High frequency on-line double conversion technology
- DSP (Digital signal processors) control technology
- Active power factor correction (APFC), input power factor up to 0.99
- Output power factor 0.9
- Wide input voltage range (110V ~ 300Vac) and frequency range (40 ~ 70Hz)
- Auto sensing frequency
- 50/60Hz frequency conversion
- Cold start
- Rear ventilation design and variable speed fan
- Effective software and hardware protection
- Quick and stable charging, 90% capacity restored in 3 h (standard model UPS)
- Linear derating in low voltage input reducing battery discharging times
- Settable delayed start when power is restored
- Advanced battery management (ABM)
- Multiple functions settable via LCD: output voltage, EOD, auto-start, bypass mode, ECO mode and frequency conversion mode
- Multi-platform communications: RS232 (standard), USB / RS485 / SNMP / dry contacts (optional)

Available Options

- Optional USB, RS485 card, AS400 dry contacts, SNMP card, SMS alarms, EPO function, 12A charger (2-3KVA only) and built-in isolation transformer

Rear Panel

1. Overcurrent Protection
2. AC Input
3. Modem/Tel/Fax
4. DC Input
5. Outlet
6. Fan
7. RS232
8. USB (optional)
9. EPO (optional)
10. SNMP/AS400 (optional)



Optional sockets



Specifications

MODEL	EA901PS	EA901PH	EA902PS	EA902PH	EA903PS	EA903PH				
Capacity	1 KVA / 900 W		2 KVA / 1800 W		3 KVA / 2700 W					
INPUT										
Rated voltage	208 V / 220 V / 230 V / 240 Vac									
Voltage range	110 ~ 176 Vac (linear derating between 50% and 100% load); 176 ~ 280 Vac (no derating); 280 ~ 300 Vac (derating 50%)									
Frequency	40 ~ 70 Hz (auto-sense)									
Power factor	≥ 0.99									
Bypass voltage range	-25% ~ +15% (settable)									
OUTPUT										
Voltage	208 V / 220 V / 230 V / 240 Vac (settable via LCD)									
Voltage regulation	±1%									
Frequency	45 ~ 55 Hz or 55 ~ 65 Hz (synchronized range); 50 / 60 Hz ±0.1 Hz (battery mode)									
Waveform	Sinusoidal									
Crest factor	3:1									
Harmonic distortion	≤ 2% (linear load); ≤ 5% (non-linear load)									
Transfer time	Mains mode to battery mode: 0 ms Inverter mode to bypass mode: 4 ms (typical)									
Overload capability	105% ~ 125%: transfer to bypass in 1 min; 125% ~ 150%: transfer to bypass in 30 s; > 150%: transfer to bypass in 300 ms									
EFFICIENCY										
Mains mode	≥ 90%		≥ 91%		≥ 92%					
Battery mode	≥ 85%		≥ 86%		≥ 87%					
ECO mode	≥ 95%		≥ 96%		≥ 97%					
BATTERIES										
DC voltage	24 V	36 V	36 V	48 V	72 V	72 V	72 V	96 V	96 V	
Inbuilt battery	2 × 9 Ah	3 × 7 Ah	/	4 × 9 Ah	6 × 7 Ah	/	6 × 9 Ah	8 × 7 Ah	/	
Charging current (max.)	1 A		6 A	1 A		6 A	1 A		6 A	
Recharge time	8 h									
ALARMS										
Utility failure	4 s per beep									
Low battery	1 s per beep									
Overload	1 s twice beep									
UPS fault	Long beep									
COMMUNICATIONS										
RS232 (standard) / USB (optional)	Supports Windows [®] 98 / 2000 / 2003 / XP / Vista / 2008 / [®] Windows 7 / 8 / 10									
SNMP (optional)	Power management from SNMP manager and web browser									
OTHERS										
Operating temperature	0 ~ 40℃									
Relative Humidity	0 ~ 90% (non-condensing)									
Noise level	≤ 50 dB (1m)									
Dimensions (W×D×H) (mm)	144×336×214	144×414×214	144×336×214	191×418×335			191×464×335		191×418×335	
Packaged dimensions (W×D×H) (mm)	232×417×318	231×492×316	232×417×318	318×533×471			320×573×471		318×533×471	
Net weight (kg)	9.5	13	6	18	25.7	10.5	27.2	32	11	
Gross weight (kg)	10.5	14.2	7	19.5	27.4	12	29	34	12.5	

●Derate capacity to 70% in CUCF mode and to 90% when the output voltage is adjusted to 208Vac. ●All specifications subject to change without notice.
●S means standard model, H means long time model. ●Custom-made specifications are acceptable.